

**X-TREME**

## FIBERFOX X-TREME EBC25 2CH Cable

The FIBERFOX X-TREME EBC25 2CH cable connector offers a cut-proof and rodent resistant double jacket glasses yarn cable construction. Excellent cable retention is achieved using aramid yarn.

The entire cable design is encased by a black PUR outer jacket. This makes the cable assembly ideal for outdoor applications. It withstands greater impacts caused by animals and the outdoor environment. FIBERFOX X-TREME is suited for a vast array of applications, including lighting, network, PA, video, broadcast, defense & government, railway, and petrochemical. The innovative design ensures its ability for deployment in the toughest environments where constant performance and total reliability are critical.

The FIBERFOX EBC25 series has an improved temperature resistance of -46°C to 71°C. The connector's dimensions fully comply with the specifications of the MIL-DTL-83526 standard and is compatible with other connectors which use this standard.

**FIBERFOX X-TREME is now available in both multimode and singlemode.**

Benefiting from the expanded beam technology and the precision optical alignment the system creates high immunity against dust, mud, liquids, and other contaminations. The FIBERFOX hermaphroditic coupling eliminates the need for adaptors and female and male mating halves. The cable connector comes pre-assembled and is not available as a single component. The finished cable is available in standardized lengths and is packed either on a drum or airspool, and in custom lengths

All rights reserved / 01.05.2025

on request.

## Features & Benefits

- ✓ Available in multimode and singlemode
- ✓ X-TREME cable protection for demanding outdoor applications
- ✓ Rodent-resistant & cut-proof
- ✓ Extreme robust, heavy-duty, connectors IP68 (mated & unmated)
- ✓ Cables are directly extendable, no couplers required
- ✓ Wear-free connectors, > 10'000 mating cycles without any maintenance
- ✓ Jam-nut design (chassis)
- ✓ Higher temperature resistance (compared to EBC15): -46°C to 71°C (-51°F to 160°F)
- ✓ Dimensions fully comply with the specifications of the MIL-DTL-83526 and are compatible with other connectors using this standard
- ✓ No special cleaning or measurement tools required



FIBERFOX X-TREME EBC25 2CH Ordering Options

Multimode Order Code	Multimode product code	Description	Singlemode order code
1036263	NKOX2M3-FG-0-050	FF X-TREME EBC25 MM 2CH 50m OM3 airspool	1038649
1036287	NKOX2M3-FG-3-050	FF X-TREME EBC25 MM 2CH 50m OM3 CableReel GT380	1038650
1036267	NKOX2M3-FG-0-100	FF X-TREME EBC25 MM 2CH 100m OM3 airspool	1038651
1036291	NKOX2M3-FG-3-100	FF X-TREME EBC25 MM 2CH 100m OM3 CableReel GT380	1038652

1036273	NKOX2M3-FG-0-150	MM 2CH 150m OM3 airspool	1038653
1036293	NKOX2M3-FG-5-150	FF X-TREME EBC25 MM 2CH 150m OM3 CableReel GT450	1038654
1036275	NKOX2M3-FG-0-200	FF X-TREME EBC25 MM 2CH 200m OM3 airspool	1038655
1036297	NKOX2M3-FG-4-200	FF X-TREME EBC25 MM 2CH 200m OM3 CableReel HT582	1038656
1036277	NKOX2M3-FG-0-250	FF X-TREME EBC25 MM 2CH 250m OM3 airspool	1038657
1036299	NKOX2M3-FG-4-250	FF X-TREME EBC25 MM 2CH 250m OM3 CableReel HT582	1038658
1036279	NKOX2M3-FG-0-300	FF X-TREME EBC25 MM 2CH 300m OM3 airspool	1038659
1036301	NKOX2M3-FG-4-300	FF X-TREME EBC25 MM 2CH 300m OM3 CableReel HT582	1038660
1036283	NKOX2M3-FG-0-500	FF X-TREME EBC25 MM 2CH 500m OM3 airspool	1038661
1036285	NKOX2M3-FG-0-1000	FF X-TREME EBC25 MM 2CH 1000m OM3 airspool	1038662

\* Customized Cable Solutions with different lengths available upon request.

## Markets & Applications

- ✓ Defense & Government
- ✓ Railway
- ✓ Oil & Gas Station
- ✓ Video
- ✓ PA Market
- ✓ Lighting & Network

Technical Information

Product	
Title	FIBERFOX X-TREME EBC25 2CH
Gender	Hermaphroditic

Mechanical	
Tensile Strength	1'800N
Compressive load	50'000N
Lifetime (typ.)	10'000 mating cycles
Bump resistance	4000 bumps @ 40g acceleration
Vibrational sinusoidal	10-500Hz, 0.75 amplitude @ 10g acceleration

Material	
Boot	Rubber (EPDM)
Insert	Steel
Shell	Aluminium
Shell plating	Hard anodize
Strain relief	Brass

**Environmental**

<b>Flammability</b>	UL 94 V-0
<b>Protection class</b>	IP68 mated (15m for 24h acc. MIL-DTL-83526D Section 3.11.28) and unmated (1m for 24h)
<b>Compatibility</b>	MIL-DTL-83526
<b>Temperature range</b>	-46°C to +71°C (-51°F to 160°F)

**Optical**

<b>Insertion Loss Multimode</b>	Typ. 1.5dB per connection / Max. 2.5dB per connection
<b>Return Loss Multimode</b>	N/A
<b>Insertion Loss Singlemode</b>	Typ. 1.0 dB max. 2.0 dB per connection (according with IEC 61300-3-4) Max. 2.5dB per connection (acc. with IEC 61300-3-34)
<b>Return Loss Singlemode</b>	Typ. >32dB (according with IEC 61300-3-6)
<b>Optical connector</b>	EBC25
<b>Optical wiring</b>	ISO / IEC 11801

Mobile cable	
Colour	Black, matte
Core diameter	Multimode 50µm
Cladding diameter	125 µm
Cable jacket	PUR
minimal bending radius	92 mm
Number of fibers	2
Cable rentation	Aramid yarn
Weight	82 kg/km
Overall diameter	9.2 mm
Outer shield	Coated glass yarn