



## NC3MX1-TOP

3 pole male cable connector, TRUE OUTDOOR PROTECTION, gold contacts

The X-TOP series is a "heavy-duty" XLR cable connector for outdoor use. Outdoor protected by mating with related cable/chassis connector of the XLR TOP range (IP65).

Gold contacts are standard.

### Features & Benefits

- Heavy duty sealed XLR connector range for harsh and demanding environment
- Outdoor protection according to IP65
- Uses high impact UV resistant materials
- TOP-Approved in consideration of UL50E

## Technical Information

| Product         |            |
|-----------------|------------|
| Title           | NC3MX1-TOP |
| Connection Type | XLR        |
| Gender          | male       |

| Electrical                   |                             |
|------------------------------|-----------------------------|
| Capacitance between contacts | $\leq 4$ pF                 |
| Contact resistance           | $\leq 3$ m $\Omega$         |
| Dielectric strength          | 1,5 kVdc                    |
| Insulation resistance        | $> 10$ G $\Omega$ (initial) |
| Rated current per contact    | 16 A                        |
| Rated voltage                | $< 50$ V                    |

| Mechanical       |                          |
|------------------|--------------------------|
| Cable O.D.       | 5.0 - 8.0 mm             |
| Insertion force  | $\leq 20$ N              |
| Withdrawal force | $\leq 20$ N              |
| Lifetime         | $> 5000$ mating cycles   |
| Wiresize         | max. 1.5 mm <sup>2</sup> |
| Wiresize         | max. 16 AWG              |
| Wiring           | Solder contacts          |
| Locking device   | Latch lock               |

| Material        |                            |
|-----------------|----------------------------|
| Bushing         | UV-resistant rubber        |
| Contact plating | Gold (Au) over Nickel (Ni) |
| Contacts        | Brass (CuZn39Pb3)          |
| Insert          | Polyamide (PA66)           |
| Locking element | Stainless steel            |
| Shell           | Stainless steel            |
| Strain relief   | Polyacetal                 |

| Environmental       |                                      |
|---------------------|--------------------------------------|
| Approvals           | UL                                   |
| Flammability        | UL 94 V-0                            |
| Standard compliance | IEC 61076-2-103                      |
| Protection class    | IP65, UL50E enclosure type 4 (mated) |
| Solderability       | Complies with IEC 68-2-20            |
| Temperature range   | -30 °C to +80 °C                     |