



MPM12-H

12-pole male chassis connector, horizontal PCB mount

The miniCON with its flexible and compact design is perfectly suitable for multipin/industrial applications. The rugged all metal miniature connector offers a push-pull locking device and stands out by an excellent cost/performance ratio.

Features & Benefits

- Velour chromium housing
- ✓ Push-pull self-locking system.
- Rugged, precisely machined all metal design
- Gold plated contacts
- ✓ Fully loaded receptacle for horizontal PCB mount

Technical Information

| Product | |
|-----------------|---------|
| Title | MPM12-H |
| Connection Type | miniCON |
| Gender | male |



| Electrical | |
|---------------------------|----------|
| Contact resistance | ≤ 8 mΩ |
| Dielectric strength | 1 kVdc |
| Insulation resistance | > 0.5 GΩ |
| Rated current per contact | 3 A |
| Rated voltage | < 50 V |

| Mechanical | |
|--------------------|----------------------|
| Wiresize | 0,5 mm² |
| Wiresize | 20 AWG |
| Wiring | Horizontal PCB mount |
| Locking device | Push-Pull |
| Mounting direction | Rear mounting |
| Chassis shape | 14.10 mm |

| Material | |
|-----------------|-------------------------|
| Contact plating | 0.2 μm AuCo |
| Contacts | Brass (CuZn35Pb2) |
| Insert | Polyamide (PA 6.6) |
| Shell | Zinc diecast (ZnAl4Cu1) |



| Environmental | |
|-------------------|---------------------------|
| Flammability | UL 94 V-0 |
| Protection class | IP 5X |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |