

## NA-2I-DLINE

Connect your legacy audio gear to the DANTE® world. The Line I/O to DANTE® Interface is an end-of-network device. It is a breakout box which allows two channels of audio to be integrated into a DANTE® network. Simultaneously, NA-2I20-DLINE converts a DANTE® stream into analog audio signals. Hence, it is possible to use this tiny box to feed analog audio signals into the DANTE® network while at the same time receiving a mix from another DANTE® source.

Line I/O to DANTE® Interface is designed for harsh stage conditions. It therefore features lockable chassis connectors for both the audio and network connections. For fixed installations, the rubber protection can be removed. With optional mounting brackets or a rack panel, the box can be mounted below tables, in floor boxes, or in equipment racks.



## Features & Benefits

- Connect analog audio equipment to a Dante® network
- Improved Audio Parameters
- LED Ring for Status Indication
- Rack mountable
- AES67 compliant
- Enhanced ESD Protection
- Extremely robust and compact design for rugged stage conditions
- Requires a Power over Ethernet switch or a PoE injector (802.3 af/at; class 1)

## Technical Information

Product	
<b>Title</b>	NA-2I-DLINE
<b>Product family</b>	Line In to Dante Interfaces

Electrical	
<b>Power consumption</b>	< 2 watts
<b>Power supply</b>	PoE switch (Power over Ethernet) or PoE injector (according to IEEE 802.3af/at/bt)

Mechanical	
<b>Weight</b>	0.44 kg (1 pound)
<b>Dimensions (with rubber protection)</b>	l = 164 mm (6.3 inches) w = 82 mm (3.2 inches) h = 51 mm (2.0 inches)
	l = 151 mm (5.9 inches) w = 66 mm (2.6 inches) h = 41 mm (1.6 inches)

Environmental	
Standard compliance	REACH EC 1907/2006 Directive 2011/65/EU IEC 62368-1:2018 IEC 62368-1:2023 EN IEC 62368-1:2020+A11:2020 UL 62368-1:2019 UL 62368-1:2021 CSA C22.2 No. 62368-1:19
Ingress protection class	IP20
Temperature range	-5°C to +60°C
Storage temperature	-40°C to +150°C

Dante specifications	
Channels	2 INPUTS (line level)
Supported sampling rates	44.1 / 48 / 88.2 / 96 kHz
Bit depth	16, 24 and 32 Bit
Latency	Depending on the network configuration, 1 ms (standard)
Ethernet connection	100 BASE-TX (PoE support)

## Analog audio input

<b>Input impedance</b>	6.6 kOhm
<b>Input level (balanced)</b>	24 dBu max.
<b>Frequency response</b>	20 Hz to 20 kHz (+/-0.5 dB)
<b>Dynamic range</b>	> 100 dB
<b>Signal-to-noise ratio</b>	> 108 dB
<b>THD + noise</b>	0.01 % @ + 4 dBu, A-weighting
<b>Crosstalk</b>	-110 dB @ 20 kHz