



# NA2MP

3 pole XLR male – Mono 1/4" plug (tip, sleeve contact)

Wired according to IEC 268-12:

Pin 2: signal

Pin 1 and 3: connected to ground

## Features & Benefits

- ✓ Versatile, pre-wired and ready to use adapters to reliably interlock various connector systems
- ✓ Professional look and compact space saving design, based on the X Series (XLR worldwide accepted standard)
- ✓ Rugged diecast shell for best reliability.

## Technical Information

Product	
Title	NA2MP
Connection Type	Adapter

Electrical	
Contact resistance	≤ 3 mΩ (XLR)
Contact resistance	≤ 6 mΩ
Dielectric strength	1.5 kV dc / > 1 kVdc (XLR/Plug)
Insulation resistance	> 2 GΩ

Mechanical	
Wiresize	
Wiring	according to IEC 268-12 pin 2 = signal, pin 1 and 3 connected to ground
Locking device	Latch lock

Material	
Contact plating	2 µm Ag over 2 µm Ni
Contacts	Brass (CuZn39Pb3) (plug)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	gal Cu/Ni

Environmental	
Temperature range	-20 °C to +65 °C