



## NAC3MX-W

\*Discontinued\* Please see successor powerCON TRUE1 TOP series. Connectors of both series are fully compatible.

Locking male cable connector, screw terminals

The powerCON TRUE1 is a locking waterproof 16 A true mains connector. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

## **Features & Benefits**

- ✓ True mains connector with breaking capacity (CBC)
- ✓ Lockable 16 A single phase connector (USA: 20 A)
- ✓ Dust and water resistant according to IP65 in mated condition
- Easy and reliable twist lock system
- Extremely robust and reliable
- ✓ Unique Neutrik cable retention
- ENEC certified according to IEC 60320
- UL recognized components

## **Technical Information**

## NEUTRIK

| Product                       |   |
|-------------------------------|---|
| Title                         | NAC3MX-W  |
|                               |   |
| Electrical                    |   |
| Contact resistance            | ≤ 3 mΩ  |
| Dielectric strength           | 4 kVdc / 2.8 kVac                                 |
| Insulation resistance         | 0,1 G $\Omega$ (after damp heat test IEC 68-2-30) |
| Number of electrical contacts | 2 + PE  |
| Rated current per contact     | 16 A rms (USA: 20 A)                              |
| Rated voltage                 | 250 V ac  |

| Mechanical |                      |
|------------|----------------------|
| Cable O.D. | 6 - 12 mm            |
| Lifetime   | > 5000 mating cycles |
| Wiresize   | 1.0 - 2.5 mm²        |
| Wiresize   | 12 AWG               |

| Material        |                            |
|-----------------|----------------------------|
| Contact plating | 2 μm Ag                    |
| Contacts        | CuNi1Si0.2                 |
| Insert          | Polyamide (PA 6.6 30 % GR) |
| Locking element | ZuAl4Cu1                   |
| Shell           | Polyamide (PA 6.6 30 % GR) |
| Strain relief   | Polyacetal (POM)           |



| Environmental     |                 |
|-------------------|-----------------|
| Flammability      | UL 94 V-0       |
| Protection class  | IP 65 (mated)   |
| Temperature range | -30 °C - +80 °C |