



## NBL75BSX14

The rearTWIST HD Large BNC cable connector is designed for large cable diameters as used on long runs and high data rates (HD).

Like all Neutrik BNCs it offers a true 75  $\Omega$  design and is perfectly suitable for HD applications. The patented rearTWIST boot guarantees easy access even in high density applications.

Suitable cable:

Draka 1.4/6.6 AF, Percon VK8, Tesca Massimo

Crimp size:

Pin: 1.75 mm (hex)

Shield: 9.73 mm (hex)

## Features & Benefits

- “rearTWIST Principle” locking/unlocking using the easily accessible soft touch boot (Patent DE 100 48507)
- True 75  $\Omega$  design meets the stringent HDTV / DVD requirements
- Snug-fit center pin insert provides tactile feedback
- Excellent cable protection and retention
- Accessories include crimp tool and dies
- Ideal for recessed bulkheads where access to the “head” of the connector might be an issue. These connectors turn from the back and not the front.
- Leading area: Avoids tilting due to side forces to protect contacts from deformation. Guarantees a lifetime of min. 1000 mating cycles!
- Shield and jacket crimp technology prevents the problem of an exposed grounding braid on cable assemblies
- Precise Swiss machined brass parts for outstanding durability

## Technical Information

Product	
Title	NBLC75BSX14
Connection Type	BNC 75 $\Omega$
Gender	male

Electrical	
Contact resistance	$\leq 3 \text{ m}\Omega$ (inner)
Contact resistance	$\leq 2 \text{ m}\Omega$ (outer)
Dielectric strength	1,5 kVdc
Impedance	75 $\Omega$
Insulation resistance	$> 5 \text{ G}\Omega$
Rated voltage	$< 50 \text{ V}$
VSWR	$\leq 1.050 / > 32 \text{ dB}$ up to 1 GHz $\leq 1.065 / > 30 \text{ dB}$ up to 2 GHz $\leq 1.100 / > 26 \text{ dB}$ up to 3 GHz

Mechanical	
Cable O.D.	9.5 mm
Cable retention	> 30 N (Center)
Crimp size	9,73 Hex crimp (shield) acc. IEC 60803 (die designation H)
Crimp size (pin)	1,75 Hex crimp (pin) acc. IEC 60803 (die designation X)
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Wiresize	
Locking device	Bayonett
Cable anchoring	Jacket crimping

Material	
Contacts	Brass (CuZn35Pb2), 0.2 µm AuCo (Center contact)
Insert	PTFE
Shell	Brass (CuZn39Pb3)
Shell plating	Optalloy®

Environmental	
Temperature range	-30 °C to +85 °C
Contact crimpability	Complies with IEC 60803 and IEC 60352-2