



## NC4FDM3-H

\*\*\* DISCONTINUED \*\*\*

Direct replacement / successor: NC4FDM3-H-1

4 pole female receptacle, horizontal PCB mount,  
Nickel housing, silver contacts, M3 mounting holes

Universal D-size metal body XLR panel mount  
series. UL recognized component.

### Features & Benefits

- Robust "D" metal shell
- Standardized D sized 24 mm panel cutout
- PCB mount termination

## Technical Information

Product	
Title	NC4FDM3-H
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	$\leq 7$ pF
Contact resistance	$\leq 5$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10$ G $\Omega$ (initial)
Rated current per contact	10 A
Rated voltage	$< 50$ V

Mechanical	
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	D
Mounting	Mounting holes with M3 threads

Material	
Contact plating	2 µm Ag over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA66)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C