



NF2C/2B

Pair of professional `Phono Plug` (`RCA` - or `CINCH` - type) - marked 2x black.

Including 2 x 2 strain reliefs for cable O.D. 3.0 mm to 7.3 mm. Additional strain relief for cable O.D. up to 8.0 mm available as accessory.



Features & Benefits

- ✓ Makes ground before signal contact and breaks signal before ground
- ✓ No more disturbing noise and broken speaker cones
- ✓ Precisely machined to our demanding quality standards
- ✓ Neutrik unique chuck type strain relief
- ✓ Gold plated contacts
- ✓ Sleek barrel with soft touch surface and coloured shrink sleeve
- ✓ Improved ground solder lug for ease soldering

Technical Information

Product	
Title	NF2C/2B
Connection Type	Profi
Gender	male

Electrical	
Capacitance between contacts	≤ 7 pF
Contact resistance	>10G mΩ
Dielectric strength	1.5 kVdc
Insulation resistance	> 5 GΩ
Rated current per contact	depends on mating connector / A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.0 - 7.3 mm
Lifetime	> 2000 mating cycles
Wiresize (mm²)	1,5 mm²
Wiresize (AWG)	16 AWG
Wiring	Solder contacts

Material	
Contact plating	5 µm Au over 5 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	PBTP 20 % GR
Shell	Brass (CuZn39Pb3)
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 601-14
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C