



NLT8MX-BAG

8 pole male cable connector, black-chrome metal housing, chuck type strain relief, ¼" flat tabs

The speakON STX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STX Series features an all metal housing.

Features & Benefits

- ✓ Current rating 40 A continuous, 50 A audio signal with 50% duty cycle
- ✓ Robust and durable all metal housing
- ✓ Reinforced metal quick lock system for ease and precise locking
- ✓ Extra large solder contacts for up to 6mm² (AWG10) wires
- ✓ Mate with all available speakON products

Technical Information

Product	
Title	NLT8MX-BAG

Electrical

Contact resistance	< 2 mΩ (after lifetime) mΩ
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 10 GΩ
Rated current per contact	40 A rms continuous
Rated current per contact	50 A audiosignal, duty cycle 50 %
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!

Mechanical

Cable O.D.	8 - 20 mm
Cable retention	≥ 220 N (subject to cable O.D. and material)
Lifetime	> 5000 mating cycles
Wiresize	6 mm ²
Wiresize	10 AWG
Wiring	flat tabs for 1/4" (FASTON® 6.3 x 0.8 mm) or soldering

Environmental

Temperature range	-30 °C to +80 °C
-------------------	------------------