



## NSJ12HC

Stereo dual jack, full nose, mounting screw included

The 1/4" stacking jack features highest board packing density as two jacks are in a single footprint and as they fit in 1 RU.

### Features & Benefits

- Stereo dual slim jack socket for PCB mounting with switch contacts
- Highest board packing density as two jacks are in a single footprint, fit in 1 RU
- Mates with A-gauge plugs acc. EIA RS-453

## Technical Information

Product	
Title	NSJ12HC
Connection Type	Jack
Gender	female

Electrical	
Contact resistance	< 15 m $\Omega$ (Top row) and < 10 m $\Omega$ (Bottom row)
Contact resistance	< 15 m $\Omega$ (Top row) and < 10 m $\Omega$
Dielectric strength	1 kVdc
Insulation resistance	$\geq$ 1 G $\Omega$ @ 500 V dc
Rated current per contact	3 A
Rated current per contact	0,50 A @ 50 V (Switch contact)
Switching contacts	2 x 3

Mechanical	
Insertion force	< 30 N
Withdrawal force	> 10 N
Lifetime	> 10000 mating cycles
Panel thickness	1 - 3 mm
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Retention spring
Mounting direction	Rear mounting
Chassis shape	9.3 mm

Material	
Cap / Nut / Washer	PA 6.6 15% GR
Contact plating	2 µm Ag
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6.6 30 % GR) UL 94 V0

Environmental	
Standard compliance	EIA RS 453, IEC 60603-11
Solderability	Complies with IEC 60068-2-20
Temperature range	-25 °C to +70 °C